

View Online at <https://aerobasegroup.com/nsn/5930-00-066-1273>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.980 inches and 1.020 inches

**Body Length:**

Between 1.920 inches and 1.960 inches

**Body Width:**

Between 0.682 inches and 0.692 inches

**Body Height:**

1.150 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.135 inches and 0.145 inches

**Actuator Length:**

Between 2.860 inches and 2.900 inches

**Actuator Style:**

Leaf

**Actuator Width:**

Between 0.170 inches and 0.210 inches

**Actuator Free Position Height:**

Between 0.720 inches and 0.780 inches

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.5 ounces

**Switch Actuating Force:**

4.0 inch-ounces

**Actuator Movement:**

Between 0.219 overtravel inches and 0.050 differential inches and 0.125 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0