## NSN 5930-00-066-1733

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-066-1733

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

1.624 inches

**Overall Height:** 

1.531 inches

**Overall Width:** 

1.375 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.218 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.469 inches single actuator

**Nonturn Device Radius:** 

0.531 inches at 10: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 10: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-066-1733

Rotary Switch - Page 2 of 2



## **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts and rotor blades silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0