# NSN 5930-00-066-2613

Pressure Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-066-2613 |
|---|
| Thread Class:   |
| 2b all threaded hole  |
| Overall Length:   |
| 2.688 inches  |
| Overall Height:   |
| 2.406 inches  |
| Overall Width:  |
| 0.938 inches  |
| Body Height:  |
| 2.156 inches  |
| Distance Between Mounting Facility Centers:                   |
| 0.688 inches  |
| Pressure Switch Type:   |
| Gage  |
| Mounting Method:  |
| Base and threaded hole  |
| Features Provided:  |
| Tubing end seal connection                                    |
| Thready Qty Per Inch (tpi):                                   |
| 32 all threaded hole  |
| Contact Action Stimulus:                                      |
| Increase  |
| Thread Size:  |
| 0.138 inches all threaded hole                                |
| Mounting Facility Pattern:                                    |
| Two position in-line  |
| Nonpile-up Contact Arrangement:                               |
| 1 pole, single throw, normally closed, momentary action       |
| Terminal Type:  |
| Tab w/screw   |
| Contact Load Current Rating:                                  |

7.0 amperes resistive load second voltage

### **Contact Adjustability:**

Actuation point adjustable, preset

### **Contact Adjustment Range:**

+100.00/+425.00 actuation point pounds per square inch

# **Contact Adjustment Type:**

External actuation point screw

### **Contact Stimulus Rating:**

250.00 actuation point pounds per square inch

# **Contact Voltage Rating In Volts:**

277.0 ac at sea level second voltage

# **NSN 5930-00-066-2613**Pressure Switch - Page 2 of 2



| Media For Which Designed: |  |
|---------------------------|--|
| Gas or liquid             |  |
| Style Designator:         |  |
| Rectangular               |  |
| Thread Series Designator: |  |
| Unc all threaded hole     |  |
| Shelf Life:               |  |
| N/a                       |  |
| Unit Of Measure:          |  |
|                           |  |
| Demilitarization:         |  |
| No                        |  |

Fiig: A048b0