

View Online at <https://aerobasegroup.com/nsn/5930-00-066-2832>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.840 inches

Overall Height:

2.160 inches

Overall Width:

0.720 inches

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

0.720 inches

Actuator Style:

Rectangular

Actuator Height:

0.640 inches

Actuator Width:

0.380 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Mounting Surface To Terminal End Distance:

1.050 inches

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0