NSN 5930-00-066-6971

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-066-6971 **Thread Class:** 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 4.822 inches **Overall Height:** 2.500 inches **Overall Width:** 1.963 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.562 inches single actuator **Nonturn Device Radius:** 0.531 inches at 12: 00 o'clock **Individual Section Quantity:** 8 **Nonturn Device Type:** Tab at 12: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 25 each section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.625 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 25 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Clip **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:**

12.8 degrees single actuator

NSN 5930-00-066-6971

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type	Switch	Actuator	Stop	Device	Type
----------------------------------	--------	-----------------	------	---------------	-------------

Fixed stop-breakoff tab single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Clips and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0