

View Online at <https://aerobasegroup.com/nsn/5930-00-067-4468>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

1.500 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Body Diameter:

0.562 inches

Bushing Length:

Between 0.302 inches and 0.322 inches

Body Length:

0.421 inches

Actuator Diameter:

Between 0.355 inches and 0.395 inches

Actuator Height:

0.562 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNEF

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-s-8805 spec.