NSN 5930-00-067-6030

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-067-6030 **Thread Class:** 2b single mounting facility **Overall Length:** 2.250 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches First Flat Length: 0.750 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.000 inches single actuator **Individual Section Quantity: Knob Specificationial Markings:** Arrow sign **Longest Horizontal Distance Between Mounting Centers:** 1.641 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.641 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 450.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, parallel flatted, threaded hole single actuator

Terminal Type: Tab w/screw

NSN 5930-00-067-6030

Rotary Switch - Page 2 of 2



Contact	Switching	Action:
Contact	Switching	ACLION.

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0