# NSN 5930-00-067-6035

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-067-6035

## **Thread Class:**

2b single mounting facility

## **Overall Length:**

3.000 inches

# **Overall Height:**

2.812 inches

## **Overall Width:**

2.812 inches

#### First Flat Length:

0.750 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

1.000 inches single actuator

#### Individual Section Quantity:

4

## **Knob Specificationial Markings:**

Arrow sign

## Longest Horizontal Distance Between Mounting Centers:

1.641 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

1.641 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## **Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

#### Features Provided:

Actuator knob

## Thready Qty Per Inch (tpi):

24 single mounting facility

## Thread Size:

0.190 inches single mounting facility

## Contact Voltage Rating In Volts:

450.0 highest ac voltage rating at sea level

## Mounting Facility Pattern:

Four position rectangular single mounting facility

# Switch Actuator Indexing Position Quantity:

4 single actuator

#### Shaft Type:

Round, parallel flatted, threaded hole single actuator

# **Terminal Type:**

Tab w/screw

# NSN 5930-00-067-6035

Rotary Switch - Page 2 of 2



**Contact Switching Action:** 

Breaks before makes each section rear

#### Switch Actuator Positioning Increment:

90.0 degrees single actuator

# **Contact Load Current Rating:**

5.0 amperes resistive load lowest dc voltage rating at sea level

#### Style Designator:

Tap, circuit selector

#### **Thread Series Designator:**

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0