## NSN 5930-00-068-0844

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-068-0844 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 1.969 inches **Overall Height:** 1.566 inches **Overall Width:** Between 0.490 inches and 0.550 inches **Body Length:** 1.594 inches **Body Width:** Between 0.490 inches and 0.550 inches **Body Height:** 1.300 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.500 inches **Actuator Style:** Round **Actuator Diameter:** 0.250 inches **Actuator Height:** 0.375 inches **Actuator Free Position Height:** 0.375 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 

4.0 ounces

**Switch Actuating Force:** 

Between 6.0 ounces and 14.0 ounces

## NSN 5930-00-068-0844

Sensitive Switch - Page 2 of 2



## **Actuator Movement:**

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.006 differential inches and 0.016 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Thread Series Designator:** 

Unc

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0