

View Online at <https://aerobasegroup.com/nsn/5930-00-068-4207>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.656 inches

Overall Height:

0.625 inches

Overall Width:

0.625 inches

Body Diameter:

0.562 inches

Bushing Length:

0.297 inches

Body Length:

0.406 inches

Case Material:

Metal

Actuator Diameter:

0.375 inches

Actuator Height:

0.750 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 15.000 amperes inductive ac

Thread Series Designator:

Un

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0