## NSN 5930-00-068-4207

Push Switch - Page 1 of 2

**Thread Class:** 

**Body Style:** 

Bushing mounted

2a



View Online at https://aerobasegroup.com/nsn/5930-00-068-4207

Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
1.656 inches
Overall Height:
0.625 inches
Overall Width:
0.625 inches
Body Diameter:
0.562 inches
Bushing Length:
0.297 inches
Body Length:
0.406 inches
Case Material:
Metal
Actuator Diameter:
0.375 inches
Actuator Height:
0.750 inches
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.500 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 15.000 amperes inductive ac

## NSN 5930-00-068-4207

Push Switch - Page 2 of 2



Thread Series Designator:
Un
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A053a0