# NSN 5930-00-068-4226

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-068-4226

# Body Style:

Hole mounted

## Hazardous Locations/environmental Protection:

Moisture resistant and waterproof

## **Overall Length:**

3.031 inches

#### **Overall Height:**

2.812 inches

#### **Overall Width:**

0.969 inches

#### **Case Material:**

Metal

## Actuator Style:

Round

#### Actuator Diameter:

# 0.438 inches

Actuator Height:

#### - - - -

0.094 inches

# **Actuator Free Position Height:**

1.560 inches

#### Housing Height:

1.812 inches

#### Housing Length:

3.010 inches

#### Housing Width:

0.969 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.688 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.000 inches

#### Maximum Voltage Rating In Volts:

250.0 ac

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## Switch Release Force:

6.0 ounces

## Switch Actuating Force:

24.0 ounces

# NSN 5930-00-068-4226

Sensitive Switch - Page 2 of 2



**Actuator Movement:** 

0.180 overtravel inches and 0.003 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

# Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A053a0