## NSN 5930-00-068-6396

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-068-6396

Overall Length:
1.938 inches
Overall Height:
3.094 inches
Overall Width:
0.969 inches
Pressure Switch Type:
Gage
Mounting Method:
Input port
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
300.00 pounds per square inch
Thread Size:
0.125 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.00 to 250.00 actuation point pounds per square inch and +0.00/+250.00 deactuation point pounds per square inch
+0.00 to 250.00 actuation point pounds per square inch and +0.00/+250.00 deactuation point pounds per square inch Contact Adjustment Type:
Contact Adjustment Type:
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating:
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating:  3.00 differential point pounds per square inch
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating:  3.00 differential point pounds per square inch  Contact Voltage Rating In Volts:
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating:  3.00 differential point pounds per square inch  Contact Voltage Rating In Volts:  250.0 ac at sea level single voltage
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating: 3.00 differential point pounds per square inch  Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage  Pressure Connector Type:
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating:  3.00 differential point pounds per square inch  Contact Voltage Rating In Volts:  250.0 ac at sea level single voltage  Pressure Connector Type:  Inverted flare, threaded external single connection
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating:  3.00 differential point pounds per square inch  Contact Voltage Rating In Volts:  250.0 ac at sea level single voltage  Pressure Connector Type:  Inverted flare, threaded external single connection  Media For Which Designed:
Contact Adjustment Type:  External deactuation point shaft and external actuation point shaft  Contact Stimulus Rating:  3.00 differential point pounds per square inch  Contact Voltage Rating In Volts:  250.0 ac at sea level single voltage  Pressure Connector Type:  Inverted flare, threaded external single connection  Media For Which Designed:  Gas or liquid

Npt single pressure connection

## NSN 5930-00-068-6396

Pressure Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0