NSN 5930-00-068-7434

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-068-7434

Overa	II Le	ngth:

Between 1.240 inches and 1.260 inches

Overall Height:

0.630 inches

Body Diameter:

Between 0.610 inches and 0.630 inches

Mounting Slot Width:

Between 0.138 inches and 0.150 inches

Body Height:

0.330 inches

Distance Between Mounting Facility Centers:

Between 0.928 inches and 0.948 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -80.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

25.00 differential point degrees fahrenheit and 170.00 actuation point degrees fahrenheit and 185.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

NSN 5930-00-068-7434

Thermostatic Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A048b0