NSN 5930-00-068-7934



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-068-7934 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.789 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.375 inches **Overall Height:** 0.870 inches **Body Length:** 0.789 inches **Body Width:** 0.250 inches **Body Height:** Between 0.450 inches and 0.510 inches **Actuator Length:** 0.375 inches **Actuator Style:** Leaf **Actuator Free Position Height:** 0.445 inches **Actuator Adapter Style:** Leaf **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Hermetically sealed **Mounting Method:** Threaded hole **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Nonpile-up Contact Arrangement:**

2.0 ounces

Switch Release Force:

1 pole, double throw, one position momentary single switch unit

NSN 5930-00-068-7934 Sensitive Switch - Page 2 of 2

A053a0



Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 0.078 pretravel inches and 0.015 overtravel inches and 0.015 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: