NSN 5930-00-068-7977

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-068-7977 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Moisture proof Overall Length: 0.560 inches **Overall Height:** 1.780 inches **Overall Width:** 0.560 inches **Body Diameter:** 0.560 inches **Bushing Length:** 0.620 inches **Body Length:** 0.630 inches **Case Material:** Metal **Actuator Length:** 0.370 inches **Actuator Style:** Rectangular **Actuator Height:** 0.250 inches **Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 120.0 ac and 28.0 dc **End Application:** C-5 c141 aircraft **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.500 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, both positions maintained single switch unit

NSN 5930-00-068-7977

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 15.000 amperes inductive ac

Thread Series Designato	r:
-------------------------	----

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0