NSN 5930-00-068-9026

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-068-9026

Thread Class:
3b single pressure connection
Inside Diameter:
0.438 inches single connection
Thread Length:
0.370 inches single pressure connection
Overall Length:
3.000 inches
Body Length:
2.130 inches
Overall Diameter:
1.375 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Clamp
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
75.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
600.0 milliamperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
9.00 actuation point pounds per square inch gage and 11.50 actuation point pounds per square inch gage and 0.50 differential point
pounds per square inch gage and 2.00 differential point pounds per square inch gage
Contact Voltage Rating In Volts:

Pressure Connector Type:
Plain, threaded internal single connection

30.0 dc at sea level single voltage

NSN 5930-00-068-9026Pressure Switch - Page 2 of 2



Media For Which Designed:
Liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0