NSN 5930-00-068-9026

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-068-9026

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Thread Length:

0.370 inches single pressure connection

Overall Length:

3.000 inches

Body Length:

2.130 inches

Overall Diameter:

1.375 inches

Pressure Switch Type:

Differential

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Clamp

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

75.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

600.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

9.00 actuation point pounds per square inch gage and 11.50 actuation point pounds per square inch gage and 0.50 differential point

pounds per square inch gage and 2.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

NSN 5930-00-068-9026

Pressure Switch - Page 2 of 2



Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0