

View Online at <https://aerobasegroup.com/nsn/5930-00-069-2390>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

1.336 inches

**Overall Height:**

Between 2.329 inches and 2.391 inches

**Overall Width:**

0.734 inches

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

1.336 inches

**Body Width:**

0.734 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.243 inches

**Actuator Height:**

Between 0.655 inches and 0.719 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

1.203 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

**Test Data Document:**

81349-mils8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Specification Data:**

96906-ms25306 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0