NSN 5930-00-069-5987

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-069-5987

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 1.750 inches **Overall Height:** 1.250 inches **Overall Width:** 1.250 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.375 inches single actuator **Overall Diameter:** 1.375 inches **Nonturn Device Radius:** 0.562 inches at 3: 00 o'clock **Individual Section Quantity: Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Pole Quantity:** 3 single section rear **Throw Quantity:** 3 single section rear **Mounting Method:** Threaded bushing single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round single actuator **Terminal Type:**

Tab, solder lug

NSN 5930-00-069-5987

Rotary Switch - Page 2 of 2



| Cc | nta | ct S | witcl | hina | Actic | 'n. |
|----|------|------|-------|------|-------|-----|
| v | nıta | UL O | WILL | ши | Actic | " . |

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

3.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0