NSN 5930-00-069-7110

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-069-7110 **Body Style:** Bushing/hole mounted **Overall Length:** 1.281 inches **Overall Height:** 2.500 inches **Overall Width:** 0.957 inches **Bushing Length:** Between 0.495 inches and 0.505 inches **Body Length:** 1.281 inches **Body Width:** 0.563 inches **Body Height:** 1.636 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.276 inches and 0.286 inches **Actuator Height:** Between 0.297 inches and 0.359 inches **Actuator Free Position Height:** Between 0.792 inches and 0.864 inches **Actuator Adapter Style:** Pushbutton **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 3 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit **Switch Release Force:**

4.0 ounces

Switch Actuating Force:

56.0 ounces

NSN 5930-00-069-7110

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.125 pretravel inches and 0.156 overtravel inches and 0.093 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0