NSN 5930-00-069-9902

Sensitive Switch - Page 1 of 2

80.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-069-9902

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.640 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.032 inches
Overall Height:
1.180 inches
Overall Width:
0.470 inches
Body Length:
1.400 inches
Body Width:
0.470 inches
Body Height:
0.680 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.175 inches
Actuator Height:
0.370 inches
Actuator Free Position Height:
0.500 inches
Maximum Voltage Rating In Volts:
115.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
12.0 ounces
Switch Actuating Force:

NSN 5930-00-069-9902

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0