NSN 5930-00-070-0006

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-070-0006

| Thread Class: |
|---|
| 3a single threaded bushing |
| Thread Length: |
| 0.340 inches single threaded bushing |
| Overall Length: |
| 4.940 inches |
| Body Diameter: |
| 0.250 inches |
| Body Length: |
| 4.140 inches |
| Tempurature Sensing Element Type: |
| Immersion well |
| Width Across Flats: |
| 1.375 inches |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Electrical box connector |
| Thready Qty Per Inch (tpi): |
| 20 single threaded bushing |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.500 inches single threaded bushing |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Terminal Type: |
| Connector, receptacle |
| Contact Load Current Rating: |
| 5.0 amperes resistive load single voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 180.00 actuation point degrees fahrenheit and 165.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 125.0 ac at sea level single voltage |
| Media For Which Designed: |
| Gas |
| Style Designator: |
| Cylindrical w/flange |
| Thread Series Designator: |

Unf single threaded bushing

NSN 5930-00-070-0006

Thermostatic Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0