

View Online at <https://aerobasegroup.com/nsn/5930-00-070-1853>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof and shock proof and vibration resistant

**Bushing Length:**

0.450 inches

**Body Length:**

0.700 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.153 inches

**Actuator Height:**

0.098 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

24.0 ounces

**Actuator Movement:**

Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc

**Special Features:**

Hydraulec actuator sensing

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0