NSN 5930-00-070-1853

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-070-1853

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Dustproof and shock proof and vibration resistant
Bushing Length:
0.450 inches
Body Length:
0.700 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.153 inches
Actuator Height:
0.098 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thread Size:
0.250 inches
0.250 inches Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches Contact Load Current Rating At Maximum Rated Voltage:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc Special Features:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc Special Features: Hydraulec actuator sensing
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc Special Features: Hydraulec actuator sensing Thread Series Designator:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Switch Actuating Force: 24.0 ounces Actuator Movement: Between 0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc Special Features: Hydraulec actuator sensing Thread Series Designator: Unf

NSN 5930-00-070-1853

Sensitive Switch - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0