NSN 5930-00-070-1866

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-070-1866

| Pody Styles |
|--|
| Body Style: |
| Bushing mount |
| Overall Length: 1.340 inches |
| |
| Overall Height: |
| Between 2.615 inches and 2.645 inches |
| Overall Width: 1.660 inches |
| |
| Bushing Length: 0.470 inches |
| |
| Body Length: |
| 1.340 inches |
| Body Width: |
| 1.660 inches |
| Body Height: |
| Between 1.085 inches and 1.115 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| Between 0.405 inches and 0.435 inches |
| Actuator Height: |
| Between 0.775 inches and 0.805 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Actuator Position-locking Relationship: |
| Up position locked in and down position locked in |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Mounting Surface To Terminal End Distance: 1.370 inches |
| |
| Inclosure Type: |
| Fully enclosed |
| Thready Qty Per Inch (tpi): |
| 32 Thread Since |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |
| Criticality Code Justification: |

Feat

NSN 5930-00-070-1866

Toggle Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 12.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

Special Features:

Weapon system essential

Test Data Document:

36659-740544-101 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0