NSN 5930-00-071-1484

Pressure Switch - Page 1 of 1



Longest Horizontal Distance Between Mounting Centers: 2.125 inches Longest Vertical Distance Between Mounting Centers: 2.125 inches Pressure Switch Type: Differential Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 7.00 differential point pounds per square inch
2.125 inches Longest Vertical Distance Between Mounting Centers: 2.125 inches Pressure Switch Type: Differential Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Longest Vertical Distance Between Mounting Centers: 2.125 inches Pressure Switch Type: Differential Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
2.125 inches Pressure Switch Type: Differential Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Pressure Switch Type: Differential Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Differential Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Mounting Method: Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Flange Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Thready Qty Per Inch (tpi): 20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
20 second pressure connection Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Contact Action Stimulus: Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Increase Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Thread Size: 0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
0.4375 inches first pressure connection Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Mounting Facility Pattern: Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Four position rectangular Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Terminal Type: Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Connector, receptacle Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Contact Stimulus Rating:
•
7.00 differential point pounds per square inch
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Media For Which Designed:
Gas or liquid
Thread Series Designator:
Unf second pressure connection
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A048b0