## NSN 5930-00-072-3089

Rotary Switch - Page 1 of 2

3.0 amperes resistive load ac at sea level



View Online at https://aerobasegroup.com/nsn/5930-00-072-3089

Hazardous Locations/environmental Protection:	
Dustproof	
Overall Length:	
5.875 inches	
Overall Height:	
2.328 inches	
Overall Width:	
2.328 inches	
Individual Section Quantity:	
1	
Knob Manufacturer Code:	
91929	
Knob Manufacturer Part Number:	
911agb011bb	
Knob Specificationial Markings:	
Turn to start push to stop circ pump	
End Application:	
Forrestal class cv, catapult/arresting gear.	
Switch Contact Basic Design:	
Nonpile-up nonsymmetrical	
Mounting Method:	
Base single mounting facility	
Features Provided:	
Cam actuated	
Contact Voltage Rating In Volts:	
300.0 ac at sea level	
Switch Actuator Momentary Position:	
Clockwise single actuator	
Cam Actuated Switch Contact Arrangement:	
2 two circuit, double break/double make, both positions maintained single switch single section in-line	
Switch Actuator Indexing Position Quantity:	
3 single actuator	
Criticality Code Justification:	
Feat	
Terminal Type:	
Tab w/screw	
Contact Switching Action:	
Breaks before makes single section in-line	
Switch Actuator Positioning Increment:	
90.0 degrees single actuator	
Contact Load Current Rating:	

## NSN 5930-00-072-3089

Rotary Switch - Page 2 of 2



Special	Features:
---------	-----------

Weapon system essential

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A052b0