

View Online at <https://aerobasegroup.com/nsn/5930-00-073-1893>

Thread Class:

2a single mounting facility

Thread Length:

0.440 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.720 inches

Overall Height:

1.570 inches

Overall Width:

1.040 inches

First Flat Length:

0.470 inches single actuator

Flat Height:

0.210 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

1.120 inches single actuator

Nonturn Device Radius:

0.432 inches at 3:00 o'clock

Individual Section Quantity:

7

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-55.0 to 105.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks, breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Special Features:

0.110 in. Diameter hole 0.062 in. Deep on flat of shaft

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0