NSN 5930-00-074-0265

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-074-0265

Hazardous	Locations	/environn	nental	Protection:
nazaruvus	LUCALIUIIS	envii onii	ıcıılaı	FIOLECTION.

Moisture proof

Overall Length:

8.782 inches

Shaft Length:

1.000 inches single actuator

Overall Diameter:

2.812 inches

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

15

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

7 each section rear

Mounting Facility Circle Radius:

1.812 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

NSN 5930-00-074-0265

Rotary Switch - Page 2 of 2



Sty				

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0