

View Online at <https://aerobasegroup.com/nsn/5930-00-075-7833>

Thread Class:

2a single mounting facility

Thread Length:

0.234 inches single mounting facility and 0.266 inches single mounting facility

Overall Length:

2.218 inches

First Flat Length:

0.422 inches single actuator and 0.454 inches single actuator

Flat Height:

0.203 inches single actuator and 0.235 inches single actuator

Shaft Diameter:

0.234 inches single actuator and 0.266 inches single actuator

Shaft Length:

0.734 inches single actuator and 0.766 inches single actuator

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Terminals silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0