# NSN 5930-00-075-8310

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-075-8310

## **Body Style:**

Bushing mounted

#### **Overall Length:**

3.081 inches

# **Overall Height:**

1.490 inches

## **Overall Width:**

1.090 inches

#### Actuator Style:

Roller plunger

### Actuator Free Position Height:

1.781 inches

#### Actuator Roller Diameter:

0.500 inches

#### Actuator Roller Width:

## 0.120 inches

Housing Diameter:

1.090 inches

## Housing Length:

1.300 inches

## Housing Bushing Length:

0.794 inches

### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Threaded bushing

## Thread Size:

0.625 inches

### Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

64.0 ounces

#### Switch Actuating Force:

144.0 inch-ounces

### **Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes lamp dc and 5.000 amperes resistive ac

# **Thread Series Designator:**

Unef

# NSN 5930-00-075-8310

Sensitive Switch - Page 2 of 2



# Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0