## NSN 5930-00-076-2564

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-076-2564

Thread Len	gth:
------------	------

0.375 inches single mounting facility

**Overall Length:** 

2.031 inches

**Overall Height:** 

1.330 inches

**Overall Width:** 

1.300 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.484 inches single actuator

**Nonturn Device Radius:** 

0.531 inches at 9: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Key at 9: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

67.5 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-076-2564

Rotary Switch - Page 2 of 2



Contact	l oad	Current	Rating:
CUIIIACI	∟∪au	Guireiii	naumu.

1.0 amperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0