NSN 5930-00-076-2564

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-076-2564

| Thread Le | ngth: |
|-----------|-------|
|-----------|-------|

0.375 inches single mounting facility

Overall Length:

2.031 inches

Overall Height:

1.330 inches

Overall Width:

1.300 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.484 inches single actuator

Nonturn Device Radius:

0.531 inches at 9: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Key at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

67.5 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-076-2564

Rotary Switch - Page 2 of 2



| Contact | l oad | Current | Rating: |
|----------|-------|----------|---------|
| CUIIIACI | ∟∪au | Guireiii | naumu. |

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0