

View Online at <https://aerobasegroup.com/nsn/5930-00-076-3017>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Explosion proof

Body Diameter:

1.500 inches

Bushing Length:

1.000 inches

Body Length:

1.750 inches

Actuator Style:

Round

Actuator Diameter:

0.625 inches

Actuator Free Position Height:

1.750 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

Between 64.0 ounces and 112.0 ounces

Actuator Movement:

Between 0.075 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0