

View Online at <https://aerobasegroup.com/nsn/5930-00-076-3017>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

1.500 inches

**Bushing Length:**

1.000 inches

**Body Length:**

1.750 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.625 inches

**Actuator Free Position Height:**

1.750 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

16.0 ounces

**Switch Actuating Force:**

Between 64.0 ounces and 112.0 ounces

**Actuator Movement:**

Between 0.075 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0