

View Online at <https://aerobasegroup.com/nsn/5930-00-076-3244>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

2.094 inches

Overall Width:

0.687 inches

Bushing Length:

0.470 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.040 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.326 inches

Actuator Height:

0.569 inches

Actuator Free Position Height:

1.719 inches

Maximum Voltage Rating In Volts:

400.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 13.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.219 overtravel inches and 0.0004 differential inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 2.000 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0