## NSN 5930-00-076-3244



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-076-3244 **Thread Class:** 2a **Body Style:** Bushing/hole mounted **Overall Length:** 1.940 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Overall Height:** 2.094 inches **Overall Width:** 0.687 inches **Bushing Length:** 0.470 inches **Body Length:** 1.940 inches **Body Width:** 0.687 inches **Body Height:** 1.040 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Actuator Style:** Round **Actuator Diameter:** 0.326 inches **Actuator Height:** 0.569 inches **Actuator Free Position Height:** 1.719 inches **Maximum Voltage Rating In Volts:** 400.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed

**Mounting Method:** 

Threaded bushing

**Thread Size:** 

0.500 inches

## **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

## **Switch Release Force:**

4.0 ounces

## NSN 5930-00-076-3244

Sensitive Switch - Page 2 of 2



Switch	<b>Actuating</b>	Force:
--------	------------------	--------

Between 9.0 ounces and 13.0 ounces

**Actuator Movement:** 

Between 0.015 pretravel inches and 0.219 overtravel inches and 0.0004 differential inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

250.000 milliamperes resistive dc and 2.000 amperes resistive ac

**Thread Series Designator:** 

Unf

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0