NSN 5930-00-076-3247

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-076-3247

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
2.000 inches
Body Width:
0.687 inches
Body Height:
1.109 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Switch Actuator Quantity:
1
Actuator Free Position Height:
0.906 inches
Maximum Voltage Rating In Volts:
250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
0.25 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
Actuator Movement: Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage:
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc Terminal Type And Quantity:
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc Terminal Type And Quantity: 3 screw
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc Terminal Type And Quantity: 3 screw Shelf Life:
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc Terminal Type And Quantity: 3 screw Shelf Life: N/a
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc Terminal Type And Quantity: 3 screw Shelf Life: N/a
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc Terminal Type And Quantity: 3 screw Shelf Life: N/a Unit Of Measure:
Between 0.156 pretravel inches and 0.141 overtravel inches and 0.003 differential inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc Terminal Type And Quantity: 3 screw Shelf Life: N/a Unit Of Measure: Demilitarization: