

View Online at <https://aerobasegroup.com/nsn/5930-00-076-8915>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Height:

0.990 inches

Overall Width:

0.990 inches

Body Diameter:

0.990 inches

Bushing Length:

Between 0.410 inches and 0.470 inches

Body Length:

1.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.350 inches and 0.410 inches

Actuator Height:

Between 0.250 inches and 0.310 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 1.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNS

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0