

View Online at <https://aerobasegroup.com/nsn/5930-00-076-8953>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant and humidity resistant

Overall Length:

Between 1.499 inches and 1.531 inches

Overall Width:

Between 0.734 inches and 0.766 inches

Body Diameter:

Between 0.484 inches and 0.516 inches

Bushing Length:

Between 0.484 inches and 0.516 inches

Body Length:

Between 0.109 inches and 0.141 inches

Actuator Height:

Between 0.296 inches and 0.328 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 8.000 amperes inductive dc and 4.000 amperes lamp dc and 10.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0