

View Online at <https://aerobasegroup.com/nsn/5930-00-077-0194>

Thread Class:

2a single threaded bushing

Thread Length:

0.500 inches single threaded bushing

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

5.280 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

4.060 inches

Tempurature Sensing Element Type:

Expanding shell

Width Across Flats:

1.000 inches

Mounting Method:

Threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.875 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

-100.00 to 400.00 actuation point degrees fahrenheit and -100.00 to 400.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Stimulus Rating:

275.00 actuation point degrees fahrenheit and 263.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0