## NSN 5930-00-079-1266

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-079-1266
Overall Length:
4.075 inches
Body Diameter:
2.030 inches
Body Length:
2.945 inches
Unthreaded Mounting Hole Diameter:
Between 0.198 inches and 0.204 inches
Longest Horizontal Distance Between Mounting Centers:
2.781 inches
<b>Shortest Horizontal Distance Between Mounting Centers:</b>
1.391 inches
Longest Vertical Distance Between Mounting Centers:
2.500 inches
Pressure Switch Type:
Gage
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
8000.00 actuation point feet and 7500.00 deactuation point feet
Contact Voltage Rating In Volts:
24.0 dc at sea level single voltage
Drocoure Connector Type

**Pressure Connector Type:** 

Plain, threaded internal single connection

## NSN 5930-00-079-1266

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Cylindrical w/mounting lugs
Thread Series Designator:
Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0