## NSN 5930-00-079-3976

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-079-3976

| Center To Center Distance Between Mounting Facilities Parallel To Length:                |
|--|
| 0.520 inches   |
| Body Length:   |
| 1.250 inches   |
| Body Width:  |
| 0.688 inches   |
| Body Height:   |
| 0.500 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.101 inches   |
| Switch Actuator Quantity:  |
| 1  |
| Actuator Free Position Height:   |
| 0.556 inches   |
| Maximum Voltage Rating In Volts:   |
| 250.0 ac   |
| Nonpile-up Contact Arrangement:  |
| 1 pole, single throw, normally closed, double break, momentary action single switch unit |
| Switch Release Force:  |
| 4.0 ounces   |
| Switch Actuating Force:  |
| 8.0 ounces   |
| Actuator Movement:   |
| Between 0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 10.000 amperes resistive ac  |
| Terminal Type And Quantity:  |
| 2 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A053a0   |
|  |