

View Online at <https://aerobasegroup.com/nsn/5930-00-079-6438>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

1.940 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Overall Height:**

1.135 inches

**Overall Width:**

0.650 inches

**Body Length:**

1.940 inches

**Body Width:**

0.650 inches

**Body Height:**

0.990 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.164 inches and 0.172 inches

**Actuator Length:**

1.084 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.900 inches

**Actuator Roller Diameter:**

0.156 inches

**Actuator Roller Width:**

0.094 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

8.0 ounces

**Switch Actuating Force:**

Between 30.0 ounces and 70.0 ounces

**Actuator Movement:**

0.085 pretravel inches and 0.028 overtravel inches and 0.023 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 4.000 amperes motor dc and 1.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0