

View Online at <https://aerobasegroup.com/nsn/5930-00-079-6438>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.135 inches

Overall Width:

0.650 inches

Body Length:

1.940 inches

Body Width:

0.650 inches

Body Height:

0.990 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.164 inches and 0.172 inches

Actuator Length:

1.084 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.900 inches

Actuator Roller Diameter:

0.156 inches

Actuator Roller Width:

0.094 inches

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

Between 30.0 ounces and 70.0 ounces

Actuator Movement:

0.085 pretravel inches and 0.028 overtravel inches and 0.023 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 4.000 amperes motor dc and 1.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0