

View Online at <https://aerobasegroup.com/nsn/5930-00-079-6688>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Overall Length:**

2.624 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.993 inches and 1.007 inches

**Overall Height:**

1.266 inches

**Overall Width:**

0.641 inches

**Bushing Length:**

0.406 inches

**Body Length:**

Between 1.796 inches and 1.828 inches

**Body Width:**

Between 0.625 inches and 0.657 inches

**Body Height:**

Between 0.625 inches and 0.657 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.140 inches and 0.150 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.245 inches and 0.255 inches

**Actuator Height:**

0.219 inches

**Actuator Free Position Height:**

Between 0.745 inches and 0.755 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.375 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

3.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.100 overtravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0