NSN 5930-00-080-2570

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-080-2570

Body Style:
Hole mounted
Overall Length:
1.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
1.010 inches
Overall Width:
0.620 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.875 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.101 inches
Actuator Style:
Round
Actuator Height:
0.065 inches
Actuator Free Position Height:
0.185 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Release Force:
8.0 ounces
Switch Actuating Force:
Between 20.0 ounces and 36.0 ounces
Actuator Movement:
Retween 0.070 pretrayel inches, and 0.010 overtrayel inches and 0.025 differential inches and 0.045 differential inches

10.000 amperes resistive ac

Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-00-080-2570

Sensitive Switch - Page 2 of 2

A053a0



Terminal Type And Quantity:
8 tab, solder lug
Reference Number Differentiating Characteristics:
Quality controlled for polaris
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: