NSN 5930-00-080-2570

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-080-2570

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 1.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.500 inches |
| Overall Height: |
| 1.010 inches |
| Overall Width: |
| 0.620 inches |
| Body Length: |
| 1.250 inches |
| Body Width: |
| 0.500 inches |
| Body Height: |
| 0.875 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.101 inches |
| Actuator Style: |
| Round |
| Actuator Height: |
| 0.065 inches |
| Actuator Free Position Height: |
| 0.185 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit |
| Switch Release Force: |
| 8.0 ounces |
| Switch Actuating Force: |
| Between 20.0 ounces and 36.0 ounces |
| Actuator Movement: |
| Retween 0.070 pretrayel inches, and 0.010 overtrayel inches and 0.025 differential inches and 0.045 differential inches |

10.000 amperes resistive ac

Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-00-080-2570

Sensitive Switch - Page 2 of 2

A053a0



| Terminal Type And Quantity: |
|---|
| 8 tab, solder lug |
| Reference Number Differentiating Characteristics: |
| Quality controlled for polaris |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |