

View Online at <https://aerobasegroup.com/nsn/5930-00-081-1883>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.250 inches

Overall Height:

0.875 inches

Overall Width:

0.750 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure and cam actuated

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.344 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest dc voltage rating at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, single throw, both positions maintained single switch single section in-line

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section in-line

Contact Load Current Rating:

1.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0